

# Laserliner®

## VideoFlex G2

FibreCamera G2 Micro 1,5 m



**1,5 m**  
Focus 5 cm

Professional video inspection system  
for visually inspecting areas that are  
difficult to access



Camera head (ø 6 mm) with LED-Lighting 3,0" LCD

- The camera head at a FlexCamera transfers pictures directly to a LCD-Monitor.
- **Problem locating:** the camera indicates what is behind or in objects, walls circuits or cables etc. even under worst light conditions, due to the LED-lighting.
- **REC-Function:** still picture and video can be recorded for a later analysis.
- **Waterproof camera head and cable.**
- **Ideal for difficult accessibility areas** due to the very small measuring head (ø 6 mm)
- **Multilingual On-Screen-Display**
- **Camera unit can be replaced** to suit application
- **Rotation:** The manual image rotation function enables the image to be rotated by 180° on the monitor.
- **Formattable SDHC-Card**
- **Webcam function**

### TECHNICAL DATA

<b>CAMERA HEAD</b>
ø 6 mm, waterproof, IP 68
<b>CAMERA FOCUS</b> 5 cm
<b>SCREEN TYPE</b> 3,0" LCD
<b>RESOLUTION DISPLAY</b> 320 x 240 pixel
<b>RESOLUTION PICTURE / VIDEO</b> 1280 x 960 pixel / 320 x 240 pixel
<b>FORMAT PICTURE / FORMAT VIDEO</b> JPEG / AVI
<b>LED</b> 3 luminosity degrees
<b>ZOOM</b> 4 x digital zoom in 10% steps
<b>MEMORY</b> 32 MB / Supports up to max. 8 GB SDHC card
<b>LENGTH OF FLEX CABLE</b> 1,5 m
<b>INTERFACE</b> USB 1.1
<b>AUTO SHUT OFF</b> 5 min
<b>POWER SUPPLY</b> 4 x AA 1,5 Volt batteries
<b>WEIGHT</b> incl. batteries and flexcamera 0,65 kg



### VideoFlex G2

inclusive carrying case  
+ FibreCamera G2 Micro 1,5 m  
+ software for webcam function  
+ batteries

**Packing dimension** (W x H x D)  
450 x 375 x 125 mm

ARTICLE	ARTICLE NO.	EAN CODE	PU
VideoFlex G2 Micro	082.111A	4 021563 683581	2

#### DISPLAY

320 x 240 pixel

3" LCD

180°

ZOOM 4x

#### CAMERA

320 x 240 pixel

LED LIGHT

IP 68

REC

SD

USB

4x AA

HARD